



ATS-RG59-182-*

RG59/U 20 Awg w/18-2C



CONSTRUCTION

COAX CABLE

Component	Inches	mm
Center Conductor		
20 Awg Solid Bare Copper	.032	0.81
Dielectric / Foam PE	.144	3.66
Shield		
95% Bare Copper Wire Braiding	.168	4.26
Jacket / PVC	.240	6.10
Nominal Jacket Wall Thickness	.034	0.86

2-18 Awg

Component	Inches	mm
Center Conductor		
18 Awg (7x0.0152 in) Bare Copper	.035	0.90
Conductors / Black & Red FR-PVC	.071	1.80
Jacket / PVC	.197	5.00
Nominal Jacket Wall Thickness	.020	0.50

MECHANICAL CHARACTERISTICS

Minimum Bend Radius	Load: 20 Times Cable O.D.
	Unloaded: 10 Times Cable O.D.
Max Temperature Rating	60°C

ELECTRICAL CHARACTERISTICS

Nominal Impedance	75 +/- 3 Ohms
Nominal Velocity of Propagation	82%
Nominal Capacitance	16.7 pF / FT
DCR of Coax Center Conductor	10.5 Ohm / 1000FT
DCR of Shield	2.70 Ohm / 1000FT
DCR of 18 Awg	6.80 Ohm / 1000FT
SRL	20 dB (10 thru 300 MHz)
	Swept Tested

Jacket Color: Black, White

PACKAGING

500 FT
Spool in a Box
500 FT
Wood Reel/Carton

APPROVALS

ISO 9001
UL, cUL, CSA
ETL
UL Listed CMX, CM, CMR
ANS/TIA/EIA 568B.2
NEC/CEC: CMR

ATTENUATION @68°F (20°C)

Frequency (MHz)	Max (dB/100 ft)	Max (dB/100 m)
10	0.84	2.75
50	1.88	6.16
100	2.71	8.89
200	3.94	12.92
400	5.85	19.18
700	8.42	27.61
900	9.83	32.23
1000	10.20	33.44



"Building Reliable Results"

www.atrasusa.com

704-966-0324